Sib XL

Cabinet > ABS structure, for low vibrations and resonances. > Aerodynamic ports for reduced distorsion and 5" Polyflex bass cone dynamic compression. > High power handling. > Polyfix system for on wall or stand mounting. > 4 layers voice-coil for dynamic bass. OAL 3/4" aluminum dome tweeter > Extanded response to 35 kHz, suitable with DVD-Audio or SACD. > Low directivity. > Phase plug and short horn integrated. Crossover > OPC (Optimum Phase Crossover) for perfect > High grade capacitors and inductors. 5" Polyflex bass cone > High power handling. > 4 layers voice-coil for dynamic bass.

Features

- The high performances on wall speaker dedicated for flat screen
- The Focal sound
- Compact flat
- Versatile Polyfix system for horizontal or vertical mounting
- Very high power handling
- Hop and Bop optional stand
- "On Wall/free standing" switch
- Rotable logo
- Splashproof
- Magnetically shielded

Frequency response	67Hz to 35kHz
Sensitivity (2.83V/1M)	91dB
Power handling	100W
Crossover	3.5kHz
Nominale/min. impedance	8 ohms/4 ohms
Dimensions (HxWxD)	19 ^{7/8} "x5 ^{5/8} "x4 ^{1/4} "
	(505x142x108mm)
Weight	8.81lbs (4kg)

